

Closed Guide Bush with Stop Rings

N 552 Mini Range

d_w	d_1	d_B	l_1	l_3	Order No.	Cage length l_2 /stroke H_{max} (Selected examples)			
3	5	7	12.5	11	5003022	10/2			
			15	13	5003108	12.5/1	10/16		
			20	18	5003023	15/6	12.5/11	10/16	
4	6	8	15	13	5003024	10/6			
			25	23	5003025	20/6	15/16	10/26	
5	7	10	20	18	5003030	15/6	10/16		
			30	28	5003031	20/16	15/26	10/36	
6	8	11	20	18	5003032	15/6	10/16		
			35	33	5003033	25/16	20/26	15/36	10/46
8	10	14	25	23	5003039	20/6	15/16		
			40	38	5003040	30/16	25/26	20/36	15/46
			60	58	5003041	40/36	30/56	25/66	20/76
10	13	18	30	28	5003047	20/16			
			40	38	5003048	30/16	20/36		
			65	63	5003049	50/26	40/46	30/66	20/86
12	15	20	25	22	5003054	20/4			
			36	33	5003055	30/6	20/26		
			50	47	5003056	40/14	30/34	20/54	
			70	67	5003057	45/34	40/54	30/74	20/84
14	17	22	25	22	5003062	20/4			
			36	33	5003063	30/6	20/26		
			50	47	5003064	40/14	30/34	20/54	
			75	72	5003065	40/64	30/84	20/104	
18	22	28	45	39	5003076	30/18			
			60	54	5003077	50/8	40/28	30/48	
			92	86	5003078	50/72	40/92	30/112	

Stroke H

Dependent on length l_2 of the ball cage used.

$H_{max} = 2 (l_3 - l_2)$